







Tinuvin[®] XT 55

New HALS for Polyethylene Tapes and Monofilaments Combines Improved Processing with Excellent Stability





Advanced HALS with balanced properties combining:

- State-of-the-art Water Carry Over behavior
- Increased efficiency in production
- Outstanding light and thermal stability
- Easy to handle product form
- Excellent color stability
- Prolonged end product life
















Tinuvin® XT 55


The advanced light stabilizer for polyethylene tape and monofilament applications

Tinuvin® XT 55 is a hindered amine light stabilizer (HALS) with excellent polymer compatibility. It combines exceptionally high UV with long term thermal stability in polyethylene. In comparison to other HALS Tinuvin® XT 55 gives very low contribution to water carry over during production of polyethylene tapes and monofilaments, helping the converter to run the line at high throughput.

Outstanding in weathering stability


Tinuvin® XT 55 provides high resistance to exposure under UV radiation in both xenon and fluorescence arc conditions. It maintains performance of the end article under most stringent conditions requested by applications standards.






Excellent water carry over (WCO) properties

Water pick up during processing of monofilaments and tapes can induce fiber breaks and inconsistent drawing causing increased waste and line downtime. Conventional HALS are known to influence WCO in a negative way. Tinuvin® XT 55 contributes significantly less to WCO compared to other HALS.




Versatile product form

Tinuvin® XT 55 is supplied as attrition resistant pellets (FB). The product is easy to handle, free flowing and guarantees high working hygiene.



Very good color retention

Color retention is key in visible applications. Usage temperatures often are as high as 80°C for several hours. Products containing Tinuvin® XT 55 have a lower tendency than other HALS to shift in color when exposed to elevated temperatures.



Asia

BASF East Asia Regional Headquarters Limited Plastic Additives 45th Floor, Jardine House

No. 1 Connaught Place Hong Kong Phone: +852 2731-0111

Europe BASF Lampertheim GmbH

Plastic Additives Chemie Strasse 22 68623 Lampertheim Germany Phone: +49 621 60-0

Middle East

BASF Plastic Additives Middle East S.P.C., Bahrain International Investment Park (BIIP) Road 1518, Al Hidd. Kingdom of Bahrain Phone: +973 17 585-232 +973 17 585-235

North America

BASF Corporation Plastic Additives 100 Park Avenue Florham Park, NJ 07932 USA

Phone: +1 973 245-6000

South America

BASF S. A. Plastic Additives Sede Administrativa Av. das Nações Unidas 14.171. Morumbi 04794-000 São Paulo, SP Brasil

Phone: +55 11 2039-2797

www.plasticadditives.basf.com

The descriptions, designs, data and information contained herein are presented in good faith, and are based on BASIS current knowledge and experience. They are provided for guidance only, and do not constitute the agreed contractual quality of the product or a part of BASIS terms and conditions of sale. Because many factors may affect processing or application/use of the product, BASF recommends that the reader carry out its own investigations and tests to determine the suitability of a product for its particular purpose prior to use. It is the responsibility of the recipient of product to ensure that any proprietary rights and existing laws and legislation are observed. No warranties of any kind, either expressed or implied, including, but not limited to, warranties of merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information set forth herein, or that the products, descriptions, designs, data or information may be used without infringing the intellectual property rights of others. Any descriptions, designs, data and information given in this publication may change without prior information. The descriptions, designs, data and information furnished by BASF hereunder are given gratis and BASF assumes no obligation or liability for the descriptions, designs, data or information given or results obtained, all such being given and accepted at the reades risk. (08/2016)









